



Made in the United States of America

**Description:**

This product is designed for use in ESD controlled areas where there are ESD susceptible devices. This product is constructed out of 6 mil, clear, permanently dissipative polyethylene film. Drawing protectors are designed to provide static control packaging for holding engineering drawings or other large documents.

Amine-free.  
N-Octanoic acid free.  
Humidity independent.  
Does not promote corrosion.  
Has no measurable outgassing.

**Electrical Properties:**

Static Decay: < 2.0 sec. per FTMS 101C, Method 4046  
Surface Resistivity: 10E10 - 10E12 ohms per ASTM D-257

**Specifications:**

Polycarbonate haze: Negligible 72 hr contact  
Corrosivity: Negligible per FTMS 101C, Method 3005  
Melt Index: .050 gm/10 min. per ASTM D-1238  
Density: 0.923 gm/cc per ASTM D-1505  
Dart impact: 230 gms per ASTM D-1709  
Coefficient of friction: 0.50 per ASTM D-1894  
1% secant modulus: MD 24,000 psi per ASTM D-882  
Stiffness: MD 25,000 psi per ASTM D-882

A. B size drawing holder will hold up to an 11" x 17" sheet size.  
Wording across bottom area:



**B Size  
Document Holder**

[07456 / 47123](tel:0745647123)  
Made in America  
[DescloIndustries.com](http://DescloIndustries.com)

*Tolerances are ± 1/4" unless specified*  
Specifications and procedures subject to change without notice.

**Drawing Protector, Statfree®, 6 Mil**



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desclo.com](http://Desclo.com)  
PHONE (909) 627-8178 FAX (909) 627-7449  
DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407  
PHONE (781) 821-8370 FAX (781) 575-0172

**DRAWING NUMBER**  
07456

**DATE:**  
December  
2011