

Made in America

# Application Instructions Statfree® Dissipative Burnishing Restorer

## Description



Figure 1. Statfree® Burnishing Restorer  
Item No. 81061, 2.5 gallon cube bag-in-box

Statfree® Dissipative Burnishing Restorer is a ready-to-use formulation that renews the unique protective properties and gloss of Statfree® Dissipative Floor Finish with a minimal investment in time, effort and money. Static decay properties, surface resistance characteristics and durability of the floor finish can be extended dramatically. The Restorer extends the re-coat cycle and significantly reduces the material cost of the floor care.

## Application

Heavy to moderate traffic floors should be treated once a week. Light traffic floors should be treated 2 to 4 times per month or as needed.

### EQUIPMENT NEEDED:

- Push broom
- 1000-2000 rpm buffing machine (with a white or beige pad)
- Statfree® Burnishing Restorer

1. Dry mop the coated area to remove loose dirt from coated floor.

2. Use a clean untreated string mop to apply a thin coat of restorer onto floor. Allow it to dry 20 to 40 minutes.

3. Burnish the coated area with a 1000 to 2000 RPM burnishing machine and a clean beige burnishing pad.

4. Dry mop the entire burnished area again.

## Physical Properties

Total Solids	6 - 10%
Coverage	2,000 sq. ft./gallon
pH Value	6 - 7
Color	Light Blue
Storage Temperature	35°F - 95°F
Freeze/Thaw Stability	Passes three cycles
Drying Time	20 - 40 min. @ 55% RH
Surface Resistance	10 <sup>6</sup> - 10 <sup>9</sup> Ohms per ESD S7.1

Statfree® Burnishing Restorer does not have a set life span. The chemicals are not known to degrade over time when stored at the proper temperature conditions as stated in the Material Safety Data Sheet. We also recommend that the product be stored in its original container and be sealed when not in use.

### Limited Warranty

Desco expressly warrants that for a period of one (1) year from the date of purchase, Desco Statfree® Dissipative Burnishing Restorer will be free of defects in material (parts). Within the warranty period, the material will be tested, repaired or replaced at Desco's option, free of charge. Call our Customer Service Department at 909-627-8178 (Chino, CA) or 781-821-8370 (Canton, MA) for a Return Material Authorization (RMA) and proper shipping instructions and address. You should include a copy of your original packing slip, invoice, or other proof of purchase date. Any material under warranty should be shipped prepaid to the Desco factory. Warranty replacements will take approximately two weeks.

### Warranty Exclusions


THE FOREGOING EXPRESS WARRANTY IS MADE IN LIEU OF ALL OTHER PRODUCT WARRANTIES, EXPRESSED AND IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WHICH ARE SPECIFICALLY DISCLAIMED. The express warranty will not apply to defects or damage due to accidents, neglect, misuse, alterations, operator error, or failure to properly maintain, clean or repair products.

### Limit of Liability

In no event will Desco or any seller be responsible or liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and users assume all risk and liability whatsoever in connection therewith.

**Material Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910. 1200. Standard must be consulted for specific requirements.



**NFPA Designation 704**

Degree of Hazard:  
4 = Extreme  
3 = High  
2 = Moderate  
1 = Slight  
0 = Insignificant

**Section I - Identity (As Used on Label and List)**

STATFREE® BURNISHING RESTORER  
DESCO  
Address (Number, Street, City State and Zip Code)  
90 Hudson Road, Canton, MA 02021  
Emergency Telephone Number  
(781) 821-8370  
Date Prepared  
8-01-2007  
Signature of Preparer (optional)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

**Section II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity Common Name(s)) OSHA PEL ACGIH TLV Other Limits Recommended % (optional)  
This product does not contain any hazardous ingredient per 29 CFR 1910-1200, also does not have any reportable ingredient as per SARA TITLE III requirements.

**Section III - Physical/Chemical Characteristics**

Boiling Point	212°F	Weight Per Gallon	
Vapor Pressure (mm Hg.)	17	Melting Point	
Vapor Density (AIR = 1)	<1	Evaporation Rate (Butyl Acetate = 1)	<1

Solubility in Water  
Dilutable  
Appearance and Odor  
Light Blue

**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used)		Flammable Limits	LEL	UEL
Non-combustible		N/A	N/A	N/A
Extinguishing Media				
N/A				
Special Fire Fighting Procedures				
None.				
Unusual Fire and Explosion Hazards				
None				

**Section V - Reactivity Data**

Stability	Unstable	Conditions to Avoid
	Stable	X

**Section VI - Health Hazard Data**

Routes(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES
Health Hazards (Acute and Chronic):			
N/A			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	N/A	N/A	N/A

**Section VII - Precautions for Safe Handling and Use**

Signs and Symptoms of Exposure:  
PROLONGED INHALATION: Vapor or mist can irritate the nose and throat and cause headache and nausea. EYE CONTACT: Mild irritation to skin upon repeated or prolonged contact. Medical Conditions Generally Aggravated by exposure:  
None known  
Emergency and First Aid Procedures:  
INHALATION: Move to fresh air. SKIN CONTACT: Flush with water.  
EYE CONTACT: Flush with water. INGESTION: Drink large amount of water, call a physician.

**Section VIII - Control Measures**

Respiratory Protection (Specify Type):  
Ventilation  
Local Exhaust Yes  
Special  
Mechanical (General) Required  
Other  
Protective Gloves: Impervious  
Eye Protection: Yes  
Other Protective Clothing or Equipment:  
Work/hygenic Practices:  
N/A = Not Applicable; N/E = None Established