

#### **Grounding & Cleaning**

If the material is used on top of an already properly grounded surface, <u>grounding hardware</u> may not be necessary. Where no properly grounded surface is available, <u>grounding hardware</u> is required to provide a path-to-ground. Rtg compliance verification measurements must be made as outlined in ESD TR53 with a <u>surface resistance meter</u>.

See Tech Bulletin  $\underline{\text{TB-7000}}$  for Reztore® Surface & Mat Cleaner Application Instructions.

### Limited Lifetime Warranty:

Desco warrants for one year that Statfree<sup>®</sup> matting products will be free of defects in materials and workmanship and will guarantee dissipative/conductive mat properties for the life of the mat. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by <u>Desco Limited</u> <u>Warranty</u>.

RoHS 2, REACH, and Conflict Minerals Statement See the Desco Industries RoHS 2, REACH, and Conflict Minerals Statement: http://www.descoindustries.com/ROHS2.aspx

DESCO

See the Desco Limited Warranty: <u>http://desco.descoindustries.com/Limited-Warranty.aspx</u>

See the Desco Disclaimer: http://desco.descoindustries.com/Disclaimer.aspx

# ANSI/ESD S20.20

Electrical Properties Rtt Resistance Rtg Resistance

Specifications: Standard Document

> **Typical Values**  $1 \times 10^4$  to  $< 1 \times 10^6$  ohms  $1 \times 10^4$  to  $< 1 \times 10^6$  ohms

Flooring
Test Procedures/Method

Meets Requirements of:

ANSI/ESD STM7.1. ANSI/ESD STM7.1.

### **Physical Properties**

Material:Ethylene Propylene Diene Monomer (EPDM)1Thickness:0.625" (15.9mm)Color:2BlackTexture:2Bubble Cells

## **Tolerances:**

Width  $\pm$  0.250" Length  $\pm$  0.250" every 1 linear foot of running material.

<sup>1</sup>Rubber material is vulcanized and may contain sulfur <sup>2</sup>Color and Texture may vary between lots and mills


For Sizes and Item Numbers, Click Here



Made in the United States of America

STATFREE<sup>®</sup> i INTERLOCKING FLOOR MAT, CONDUCTIVE, ERGONOMIC, 0.625" (15.9MM)

Desco com
<u>Desco.com</u>
Desco.com



© 2023 DESCO INDUSTRIES INC. Employee Owned